

FIREFIGHTER'S PPE DRYING CABINET

SPECIFICATIONS		UTGC
Capacity - lb (kg)		6 Full Sets of Turnout Gear Space for up to 15 boots/gloves
Programmable Cycles		5
Overall Width - in (mm)	Outer	61.13 (1553)
	Innerr	53.94 (1370)
Overall Depth - in (mm)	Outer	32.75 (832)
	Innerr	29.19 (741)
Overall Height - in (mm)	Outer	79.5 (2019)
	Innerr	60 (1524)
Door Opening Size - in (mm)		180° Angle
NFPA 1851 Compliance		Yes
Electric Heating		12 kW 9 kW
Electric Connection - Circuit Breaker		208V - 50/60 Hz 1 Ph 60A Breaker 208V - 50/60 Hz 3 Ph 35A Breaker 240V - 50/60 Hz 1 Ph 70A Breaker 240V - 50/60 Hz 3 Ph 40A Breaker
Exhaust Diameter - in (mm)		6 (152)
Outlet Airflow - cfm (m3/h)		300 (510)
Net Weight - lb (kg)		570 (260)
Shipping Weight - lb (kg)		630 (290)
Agency Approvals		CSA

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

UNIMAC.COM/FIRE

AU21-0021

UniMac by Alliance Laundry Systems

